



MULTI-CONDUCTOR UNSHIELDED CMP CABLES

Gauge Size	No. of Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nominal O.D.
22	2	7	.008	.015	.122
22	3	7	.008	.015	.129
22	4	7	.008	.015	.141
22	5	7	.008	.015	.154
22	6	7	.008	.015	.168
22	8	7	.008	.015	.182
22	10	7	.008	.015	.214
22	12	7	.008	.015	.221
20	2	7	.008	.015	.134
20	3	7	.008	.015	.143
20	4	7	.008	.015	.156
20	6	7	.008	.015	.187
18	2	7	.009	.015	.157
18	3	7	.009	.015	.167
18	4	7	.009	.015	.184
18	6	7	.009	.015	.221
18	8	7	.009	.015	.241
16	2	19	.010	.015	.182
16	3	19	.010	.015	.194
16	4	19	.010	.015	.213

Construction:

Stranded bare copper conductors insulated with color coded Plenum Rated 75°C PVC, jacketed with Plenum Rated white 75°C PVC. Cables are twisted prior to jacketing. UL Rated CL3P/FPLP/CMP

COLOR CODE: Black, Red White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan

Above cables also available as pairs or triads

**(UL) NEC Article
800, 725, 760**

