



MULTI-CONDUCTOR SHIELDED CMP CABLES

Gauge Size	No. of Conductors	Stranding	Insulation Thickness	Jacket Thickness	Nominal O.D.
22	2	7	.008	.015	.127
22	3	7	.008	.015	.134
22	4	7	.008	.015	.146
22	5	7	.008	.015	.158
22	6	7	.008	.015	.175
22	8	7	.008	.015	.187
22	10	7	.008	.015	.220
22	12	7	.008	.015	.227
20	2	7	.008	.015	.138
20	3	7	.008	.015	.149
20	4	7	.008	.015	.162
20	6	7	.008	.015	.193
18	2	7	.009	.015	.163
18	3	7	.009	.015	.173
18	4	7	.009	.015	.188
18	6	7	.009	.015	.227
18	8	7	.009	.015	.246
16	2	19	.010	.015	.196
16	3	19	.010	.015	.208
16	4	19	.010	.015	.230

Construction:

Stranded bare copper conductors insulated with color coded 75°C Plenum Rated PVC, jacketed with Plenum Rated White 75°C PVC. Cables are twisted prior to jacketing. All cables have an overall aluminum / polyester shield and stranded tinned copper drain wire. UL Rated CL3P/FPLP/CMP

COLOR CODE: Black, Red White, Green, Orange, Blue, Brown, Yellow, Purple, Gray, Pink, Tan

Above cables also available as pairs or triads

**(UL) NEC Article
800, 725, 760**

